

Eagle Dual 60 255-275 Watt POLY CRYSTALLINE MODULE


Positive power tolerance of 0/+3%

ISO9001:2008 \ ISO14001:2004 \ OHSAS18001
certified factory.
IEC61215 \ IEC61730 certified products.

(Australia & NZ Market Use Only)



(4BB)



KEY FEATURES



PID Free Module:

Anti-PID cell and encapsulation technology
Frameless module requires no module grounding which may cause PID



Higher Lifetime Power Yield:

<0.5% annual power degradation
30 year linear power warranty



Saving BOS Cost:

Designed for high voltage systems of up to 1500 VDC, saving BOS cost



Improved Durability and Reliability:

Dual glass reduces micro-cracking, snail trails, corrosions caused by moisture, sand, salt mist, acid, alkali, etc. The optional Solar Super Shell Tape designed for dual glass module edge sealing helps prevent water vapor from entering the module and improve the reliability significantly.



Less Maintenance Requirement:

Reduced soiling and snow coverage requires less maintenance and enhances fire safety



Aesthetically Pleasing Design:

White encapsulation material maximizes module efficiency up to 16.72% (60-poly max. output 275W); Transparent EVA increases light transmission, ideal for installations requiring light to pass through




Strengthened Mechanical Support:

5400 Pa snow load, 2400 Pa wind load




LINEAR PERFORMANCE WARRANTY


10 Year Product Warranty • 30 Year Linear Power Warranty
0.5% Annual Degradation Over 30 years



Engineering Drawings



I



*If using shell tape, length and width will add 2mm respectively, thickness will add to 8mm.


Packaging Configuration

(Two pallets=One stack)


30pcs/pallet, 60pcs/stack, 840 pcs/ 40'HQ Container

Electrical Performance & Temperature Dependence

Current-Voltage & Power-Voltage Curves (265W)



Temperature Dependence of Isc, Voc, Pmax



Mechanical Characteristics

Cell Type Poly-crystalline 156×156mm (6 inch)

No. of cells 60 (6×10)

Dimensions 1658x992x6mm(65.27x39.05x0.24 inch, 2.5mm Glass)

Weight 24kg(53 lbs, 2.5mm Glass)

Front Glass 2.5mm High transmission, Antireflection coating, semi-tempered glass

Back Glass 2.5mm Semi-tempered glass

Junction Box IP67 Rated

Output Cables TUV 1×4.0mm²
positive – 250mm, negative- 150mm or customized

SPECIFICATIONS

Module Type	JKM255PP-DV		JKM260PP-DV		JKM265PP-DV		JKM270PP-DV		JKM275PP-DV	
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power (Pmax)	255Wp	190Wp	260Wp	194Wp	265Wp	198Wp	270Wp	202Wp	275Wp	205Wp
Maximum Power Voltage (Vmp)	30.8V	28.1V	31.1V	28.3V	31.4V	28.7V	31.7V	29.0V	32.0V	29.3V
Maximum Power Current (Imp)	8.28A	6.75A	8.37A	6.84A	8.44A	6.91A	8.52A	6.97A	8.61A	7.00A
Open-circuit Voltage (Voc)	38.0V	35.0V	38.1V	35.1V	38.6V	35.3V	38.8V	35.6V	39.1V	35.9V
Short-circuit Current (Isc)	8.92A	7.22A	8.98A	7.26A	9.03A	7.31A	9.09A	7.35A	9.15A	7.37A
Module Efficiency STC (%)	15.50%		15.81%		16.11%		16.42%		16.72%	
Operating Temperature(°C)	-40°C~+85°C									
Maximum system voltage	1500VDC (IEC)									
Maximum series fuse rating	15A									
Power tolerance	0~+3%									
Temperature coefficients of Pmax	-0.40%/°C									
Temperature coefficients of Voc	-0.30%/°C									
Temperature coefficients of Isc	0.06%/°C									
Nominal operating cell temperature (NOCT)	45±2°C									

STC: Irradiance 1000W/m² Cell Temperature 25°C AM=1.5

NOCT: Irradiance 800W/m² Ambient Temperature 20°C AM=1.5 Wind Speed 1m/s

* Power measurement tolerance: ± 3%