

Eagle Black 72P-V 315-335 Watt

POLYCRYSTALLINE MODULE

Positive power tolerance of 0~+3%

ISO9001:2008, ISO14001:2004, OHSAS18001
certified factory.

IEC61215, IEC61730 certified products.



(5BB)



KEY FEATURES



System Voltage:

The maximum voltage is promoted to 1500V and the module strings are extended by 50% which reduces the overall system BOS.



PID RESISTANT:

Eagle modules pass PID test, limited power degradation by PID test is guaranteed for mass production.



High Power Output:

With up to 335 Wp and 17.26 % efficiency, highest performing module of its kind on the market.



Low-light Performance:

Excellent performance in low-light environments.



Severe Weather Resilience:

Extremely weather resistant due to approval for increased snow and wind loads: 5400 Pa snow load, 2400 Pa wind load.




5 Busbar Solar Cell:


No power loss thanks to improved temperature co-efficient caused by 5 busbar solar cell.

LINEAR PERFORMANCE WARRANTY

10 Year Product Warranty • 25 Year Linear Power Warranty



Engineering Drawings




Packaging Configuration

(Two pallets = One stack)


26pcs/pallet, 52pcs/stack, 624 pcs/40'HQ Container

Electrical Performance & Temperature Dependence

Current-Voltage & Power-Voltage Curves (325W)



Temperature Dependence of Isc, Voc, Pmax



Mechanical Characteristics

Cell Type	Poly-crystalline 156×156mm (6 inch)
No. of cells	72 (6×12)
Dimensions	1956×992×40mm (77.01×39.05×1.57 inch)
Weight	22.5 kg (49.6 lbs.)
Front Glass	3.2mm, Anti-Reflection Coating, High Transmission, Low Iron, Tempered Glass
Frame	Anodized Aluminium Alloy
Junction Box	IP67 Rated
Output Cables	TÜV 1×4.0mm ² , Length: 900mm or Customized Length

SPECIFICATIONS

Module Type	JKM315PP-72-J4-V		JKM320PP-72-J4-V		JKM325PP-72-J4-V		JKM330PP-72-J4-V		JKM335PP-72-J4-V	
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power (Pmax)	315Wp	233Wp	320Wp	237Wp	325Wp	241Wp	330Wp	245Wp	335Wp	249Wp
Maximum Power Voltage (Vmp)	37.2V	34.7V	37.4V	34.7V	37.6V	35.0V	37.8V	35.3V	38.0V	35.6V
Maximum Power Current (Imp)	8.48A	6.71A	8.56A	6.83A	8.66A	6.89A	8.74A	6.94A	8.82A	6.99A
Open-circuit Voltage (Voc)	46.2V	42.8V	46.4V	43.0V	46.7V	43.3V	46.9V	43.6V	47.2V	43.8V
Short-circuit Current (Isc)	9.01A	7.28A	9.05A	7.35A	9.10A	7.40A	9.14A	7.45A	9.18A	7.52A
Module Efficiency STC (%)	16.23%		16.49%		16.75%		17.01%		17.26%	
Operating Temperature(°C)	-40°C~+85°C									
Maximum system voltage	1500VDC (IEC)									
Maximum series fuse rating	20A									
Power tolerance	0~+3%									
Temperature coefficients of Pmax	-0.40%/°C									
Temperature coefficients of Voc	-0.31%/°C									
Temperature coefficients of Isc	0.06%/°C									
Nominal operating cell temperature (NOCT)	45±2°C									

*STC: Irradiance 1000W/m²

Cell Temperature 25°C

AM=1.5

NOCT: Irradiance 800W/m²

Ambient Temperature 20°C

AM=1.5

Wind Speed 1m/s

* Power measurement tolerance: ± 3%